



Verdapave E30 Specification Sheet

- Paths and access road reinforcement
- Slope and embankment reinforcement
- Parking areas
- Sidewalks and garden paths
- Storage areas



Dimensions:	33 cm x 33 cm x 3 cm
Wall thickness, Wall height:	4 mm, 30 mm
Weight per tile:	0,60 kg
Weight per m ² :	5,43 kg
Loadbearing capacity:	Up to 250 t
Natural stability:	Temperature range -50 up to 90°C
Dimensional changes:	Approx. 0,5 % (at a standard temperature +20°C up to 80°C)
Humidity absorption:	0,01 %
Installation:	100 m ² per person per hour

Delivery units

Packing unit:	1 layer (= 12 tiles corresponding to 1,33 m ²)
Layers per pallet:	71
m ² per pallet:	94,43 m ²
Tiles per pallet:	852 pieces
Dimensions per one way pallet:	105 cm x 135 cm x 229 cm
Gross weight per pallet:	484 kg (pallet incl.)



Certification

Durability:	Unlimited according to TÜV certification
Charge:	Up to 10 t axle load in accordance with DIN 1072
Environmental compatibility:	Environmentally neutral in accordance with DIN 38412 UV and frost resistant
Solubility:	Resistant to acids, alkalis, oil and petrol (de-icing salt, ammonia, acid rain etc.)
Tested according to:	DIN 1072 roads and bridges DIN EN ISO 124 B125 requirements for surfaces for car park areas DIN 38412

Specialists in Geosynthetics & Erosion Control